

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
18 January 2001 (18.01.2001)

PCT

(10) International Publication Number
WO 01/03891 A1

(51) International Patent Classification⁷: **B25J 9/10, 9/02**

(21) International Application Number: PCT/SE00/01425

(22) International Filing Date: 5 July 2000 (05.07.2000)

(25) Filing Language: Swedish

(26) Publication Language: English

(30) Priority Data:
9902690-8 13 July 1999 (13.07.1999) SE

(71) Applicant (for all designated States except US): **BINÄR ELEKTRONIK AKTIEBOLAG** [SE/SE]; Batterivägen 4, S-461 38 Trollhättan (SE).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **BLOMGREN, Stefan** [SE/SE]; Kometvägen 23, S-461 59 Trollhättan (SE). **PETTERSSON, Ingemar** [SE/SE]; Utsikten 4455, S-462 93 Vänersborg (SE).

(74) Agents: **HYNELL, Magnus et al.**; Hynell Patenttjänst AB, Patron Carls väg 2, S-683 40 Hagfors/Uddeholm (SE).

(81) Designated States (*national*): AE, AG, AL, AM, AT, AT (utility model), AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CR, CU, CZ, CZ (utility model), DE, DE (utility model), DK, DK (utility model), DM, DZ, EE, EE (utility model), ES, FI, FI (utility model), GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KR (utility model), KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SK (utility model), SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW.


(84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

Published:

- With international search report.
- Before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments.

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: **ROBOT UNIT**



(57) Abstract: The present invention relates to a method for rapid transfer of a work object in both the horizontal and vertical directions using a robot unit (10) having a gripping mechanism (12) preferably from one workstation (3) to another (4), the work piece (2) weighing between one kilo and forty kilos and the transfer in the horizontal direction being at least one metre but less than ten metres and at least partially being effected along an essentially horizontally extending beam unit (20), and the gripping mechanism (12) being arranged in such a way that, at least in one end situation (E1) along the beam (20), it can collect and/or deliver a work object (2) in a position (E2) situated beyond the end situation (E1) along the said horizontal beam (20), which robot unit is controlled by means of a control unit (50) and is driven by means of a belt member (24) and at least two motors (26, 27) comprising rotor units connected to drive wheels (26A, 27A) for the said belt member (24), the said motors (26, 27) being immovably arranged in relation to the said workstations (3, 4) and the transfer of the work object (2) being effected without displacement of either of the said two motors (26, 27), characterized in that the whole of the transfer is executed along one and the same beam unit (20), in that the said belt member (24) is constituted by a single continuous drive belt (24), which, at the same time, is connected to and driven by the said drive wheels (26A, 27A), and by the displacement of the work object being guided along a pre-programmed path by means of a control computer (51) in the control unit (50) through the continuous control and registration of the situation of each of the rotors forming part of the said motors (26, 27).